

an imaging system;
an image rotator; and

a control system coupled to the polar coordinate stage and the image rotator, wherein the control system controls the image rotator and causes the image rotator to rotate an image to compensate for rotation of the rotatable platform and preserve orientations of features in the image.

2. The device of claim 1, wherein the control system applies control signals to the polar coordinate stage to control movement of the object and applies control signals to the image rotator to compensate for the rotation of the object.

3. The device of claim 2, further comprising an operator interface including a monitor for viewing the image.

4. The device of claim 3, wherein the operator interface further comprises a control coupled to send to the control system commands indicating a desired motion of the image viewed on the monitor.

5. The device of claim 1, wherein the rotatable platform has a rotation axis that intersects a linear drive axis along which the stage moves rotatable platform.

6. The device of claim 5, an optic axis of the imaging system is stationary relative to the polar coordinate stage and coincides with the linear drive axis.

7. The device of claim 1, a setting of the linear drive indicates a displacement of the linear drive relative to a zero displacement position.

8. The device of claim 1, further comprising an orientation monitoring system that measures an angular displacement of the rotatable platform relative to a zero angular displacement setting.

9. The device of claim 1, further comprising a video camera and a display monitor.

LAW OFFICES OF
SKJERVEN MORRILL
MACPHERSON LLP

25 METRO DRIVE
SUITE 700
SAN JOSE, CA 95110
(408) 453-9200
FAX (408) 453-7979

10. The device of claim 9, wherein the image rotator comprises an image capture and image processing system that captures the image from the video camera and rotates the image by an amount selected by the control system.

11. The device of claim 1, wherein the imaging system comprises a microscope.

12. The device of claim 11, wherein the image rotator comprises a rotatable dove prism on an optical axis of the microscope.

13. The device of claim 11, further comprising a video camera and a display monitor.

14. The device of claim 13, wherein the image rotator comprises a rotatable Dove prism on an optical axis of the microscope.

15. The device of claim 13, the image rotator comprises software which is capable of rotating a video image from the video camera.

16. The device of claim 1, wherein the imaging system comprises a scanning probe microscope.

17. The device of claim 1, wherein the imaging system comprises a scanning microscope.

18. The device of claim 17, further comprising an image processing system and display monitor.

19. The device of claim 17, wherein the image rotator comprises a set of beam deflectors that changes orientation of an area scanned on the surface of the object.

20. The device of claim 17, wherein the scanning microscope is a scanning electron-beam microscope.

21. The device of claim 17, wherein the scanning microscope is a scanning ion-beam

microscope.

22. The device of claim 1, wherein the imaging system comprises a confocal microscope.

23. The device of claim 22, further comprising an image processing system and a display monitor.

24. The device of claim 1, wherein the image rotator comprises a rotatable dove prism.

25. The device of claim 1, wherein the image rotator comprises software which allows rotation of a digitized image.

26. The device of claim 1, wherein the control system comprises a processor executing a module that converts Cartesian coordinate input commands relative to an image of the object to polar coordinate stage commands and image rotator commands.

27. A method for viewing an object, comprising:
mounting the object on a polar coordinate stage;
viewing an image of a region of the object;
using the polar coordinate stage to move the object; and
rotating the image of the object as the object moves so that features in the image retain a fixed orientation while the object rotates.

Please cancel Claim 28.

~~28.~~

(Amended) A measuring device comprising:
a polar coordinate stage including a rotatable platform for mounting of a sample;
an alignment system including an edge detector and a processing system that identifies a position of the sample from measurements that the edge detector takes while the polar coordinate stage rotates the sample;
a measurement system for measuring a physical property of a portion of the sample

LAW OFFICES OF
SKJERNEN MORRILL
MACPHERSON LLP

25 METRO DRIVE
SUITE 700
SAN JOSE, CA 95110
(408) 453-9200
FAX (408) 453-7979

B1
cont

35

B

B'
 cancel

that the polar coordinate stage moved into a field of view of the measurement system;
an imaging system for obtaining an image of a portion of the sample that the polar coordinate stage moved into a field of view of the imaging system; and
an image rotator that rotates the image to compensate for rotation of the sample by the polar coordinate stage.

30. The measuring device of claim 29, wherein the alignment system further comprises a pattern recognition module that identifies a feature in the image as rotated by the image rotator and from identification of the feature, determines a position of the sample.

31. The measuring device of claim 29, wherein the imaging system includes a video camera and the image rotator rotates a video image from the video camera.

32. The measuring device of claim 29, wherein the image rotator comprises an optical element for rotating the image.

B2
 cancel

~~32.~~ ²⁸ (Amended) The measuring device of claim [28] ~~29~~ wherein the alignment system further comprises a pattern recognition module that identifies a feature in the image and determines a position of the sample.

34. A measuring method comprising:
mounting a sample on a polar coordinate stage, wherein the sample as mounted has a position known to a first accuracy;
measuring edge locations of the sample while the polar coordinate stage rotates the sample;
prealigning the sample by determining the position of the sample from the edge locations, wherein the prealigning determines the position of the sample to a second accuracy;
using the polar coordinate stage to move the sample so that a view area of an imaging system contains a first feature;
rotating an image formed by the imaging system to compensate for rotation of the sample by the polar coordinate stage;
using a pattern recognition module to process the rotated image and identify a first location corresponding to the first feature; and